

ELECTRAK 1



Great for Condos!

POWER

- 1.5 HP Electric Motor
- 115 volt, input power
- Adjustable speed control provides adjustable amp draw
- Variable Frequency Drive (VFD) with G.F.I. Plug
- 25' long power cord
- Available in 220V, 1 Phase, 50 HZ

AIR

- High strength, air foil design impeller provides increased efficiencies by delivering larger volumes of air with less noise and horsepower consumption
- 2200 CFM air flow
- 9" H₂O static capability

FILTRATION

- Primary stage durable cube filter removes easily for replacement or cleaning
- Second stage pocket filter is 90-95% ASHRAE efficient
- Third stage 24" x 24" x 12" HEPA filter rated at 99.97% DOP efficient and scan tested to insure leak-free

performance



CONSTRUCTION

- ◆ Welded aluminum frame with .080" thick riveted exterior
- ◆ Compression gaskets between modules
- ◆ 5" diameter casters
- ◆ Positive locking draw latches for quick airtight connection
- ◆ 33" long x 24" wide x 60" high (VAC)
- ◆ 18" long x 24" wide x 26" high (HEPA)
- ◆ Industrial grade high visibility controls
- ◆ Magnehelic vacuum gauge
- ◆ Hourmeter and ammeter
- ◆ 12" dia. Inlet hose connection



Scooter-Vac

This is more than just a shop-vac. Its sturdy design keeps it from toppling and ensures a long life. Its 5 stage filtration permits only clean air to pass through its exhaust.



VAC100

- 115 CFM, 110" H₂O static
 - 15 gallon polyethylene tank
- *rugged *dent proof *rust proof
- 99.99% efficient at .3 microns (HEPA)
 - 2 HP electric motor with 30' cord
 - 53 lbs.
 - U/L listed
 - Includes 12 bags (6 ea. stage 1 & 2) and 10 bags (stage 4)

VAC101

Duct cleaning tool kit for Hepa Vac includes: 50' x 1-1/2" dia. Hose, (3) 36" wands, aluminum brush, (2) plastic brushes (8" & 14"), round brush, and crevice tool



Meyer Machine & Equipment, Inc.

800-728-3828 | www.meyermachine.com