

# ***The Major***

- INSTALLATION
- OPERATION
- MAINTENANCE

Meyer Machine & Equipment, Inc.  
1400 St. Paul Avenue  
Gurnee, Illinois 60031

(800) 728-3828  
(847) 395-2970  
(847) 385-9420 Fax

# The Major

## I.O.M. MANUAL

### **Safety :**

- Do not operate this equipment until you have read this manual and fully understand the machine's operation.
- Never operate this equipment in an area with poor ventilation, in a building, or inside a residence.
- Never operate the vacuum without a hose on the inlet.
- Never operate the vacuum without a hose or bag on the discharge of the fan housing.
- Never place your hands, arms or any body parts near the fan inlet or discharge while the fan is in motion. The fan can cause severe and permanent injuries to body parts.
- Never attempt any maintenance while the fan is rotating.
- Prior to any maintenance, turn the key to the off position and remove the key from the ignition. Then remove the wire from the spark plugs. This will eliminate the possibility of accidental ignition.
- Never touch the positive and negative leads of the battery. This is a 12 volt Direct Current negative ground system.
- Exercise caution when moving your vacuum up and down ramps or inclines. This machine weighs in excess of 325 lbs. and can cause injury if moved improperly.
- Do Not touch the muffler. The engine on the vacuum produces an extremely hot exhaust system and can cause severe burns if touched.
- Do Not transport the vacuum without properly securing the vacuum in your vehicle.
- Do Not continue to operate a vacuum that has an out of balance condition. This will be apparent by the machine shaking violently. Operating a machine that is out of balance could result in damage to the machine or injury to the operator.

# 1.

## The Major

### I.O.M. MANUAL

#### ***Installation :***

Upon receipt of your power vacuum and equipment, double check your packing list against the actual materials received. Note any discrepancies and/or damage to the freight on the trucker's freight bill. Any claims will have to be processed through the freight company and they will require documentation.

Unpack your **Major** power vacuum using caution not to damage the machine. Your machine should be fully assembled with the exception of the gas tank. Locate the packing slip attached to your shipment; check to see that you received everything that is listed.

If you are connecting a filter bag directly to the discharge of the vacuum, connect a 36" piece of discharge hose to the vacuum outlet and position the bag so that the 11" dia. inlet to the bag is aligned with the discharge of the fan. Using the stainless steel clamp provided, secure the discharge hose to the vacuum outlet. Using a strap clamp, mount the bag to the discharge hose. Install the gas tank using the quick couplers provided on the engine gas line and the gas tank. (If applicable)

If you are using a discharge hose to direct the material to a remote location, place your 8" diameter hose over the discharge of the vacuum and tighten strap clamp as described above. To minimize the chance of settling, limit discharge hose runs when possible, and keep discharge hose as straight as possible. Place end of hose into filtered containment area or connect filter bag.

**Warning: The muffler is hot and will cause injury.**

**Note:** Check the oil in the engine prior to starting the engine. See the Kohler Owner's Manual for these instructions.

# 2.

# The Major

## I.O.M. MANUAL

### ***Operation :***

Prior to operating your **Major** Power vacuum, there are a few necessary points that must be checked.

- Check oil level
- Inlet hose is firmly in place
- Discharge bag/hose is clamped on
- Machine is located in a well ventilated area

**NOTE: Never operate your vacuum without proper inlet and discharge connections.**

**NOTE: Never operate your vacuum inside of a building. Your vacuum produces poisonous Carbon Monoxide emissions, and will cause injury or death.**

Once you have checked the items above, you are ready to proceed with starting the vacuum.

Place the fuel switch to the on position (if applicable). Place the throttle lever midway between low and high speed, pull the choke out while you initially crank the engine. Crank the engine until it starts, then push the choke in and the engine will begin to run smoothly.

When the vacuum begins to run, arrange the filter bag so air flows through it with ease. Let the engine idle for 2-3 minutes prior to increasing the speed. The vacuum may then be brought up to operating speed, slowly.

We define "operating speed" as the speed that is necessary to effectively do the job. If the job is small, then the throttle may not need to be moved to the maximum setting. On larger jobs you will need to increase the speed to achieve the proper vacuum level. In most conditions the engine should be run at full throttle, as this is how the manufacturer designed it. Never over speed your engine by overriding engine controls.

When the vacuuming job is done, do not remove the inlet hose or the discharge bag or hose until the vacuum has come to a complete stop and the key is in the off position.

To shut down the vacuum, gradually move the throttle lever to the middle of the speed range, and then turn the key to the off position. This will minimize the possibility of the engine back-firing.

**NOTE: All warranty repairs must go through Meyer Machine & Equipment prior to any service work being done. Work not authorized by Meyer Machine & Equipment will not be covered under warranty.**

### 3.

## The Major

### I.O.M. MANUAL

#### ***Maintenance :***

Your **Major** Power vacuum, as well as the rest of your equipment, will last for many years if you properly maintain the equipment.

The **Major** requires the following regular maintenance procedures:

**NOTE: ALWAYS FOLLOW THE SAFETY GUIDELINES AS OUTLINED ON PAGE 1 OF THIS MANUAL.**

**FOR A NEW ENGINE**, change the oil after the first **5** hours of operation. Thereafter, change oil after every 100 hours of operation.

- I. Every day check the oil level by removing and checking the dip stick. Refer to the accompanying Kohler Owner's manual for the proper oil viscosity.
- II. The engine should have the oil and filter (if applicable) changed every 100 hours of operation. Drain the oil from the extended oil drain on the side of the engine opposite the muffler. Then refill the oil reservoir with the oil recommended in the accompanying Kohler Owner's manual.
- III. The bolts on the fan wheel should be checked for tightness every time you change your oil. This requires a 1/2" dia. socket wrench with an extension. Locate the (3) bolts on the bushing inside the fan inlet. Then turn each bolt clockwise until they are tight.
- IV. The air filter on the engine should be checked every 50 hours of operation. To do this, loosen the air cleaner clamp and remove the cover. Remove the air cleaner and take the pre-filter off the pleated air filter. Wash this filter off, allow it to dry and then replace the pre-filter. When you maintain the pre-filter you will not have to replace the main filter as often.
- V. The engine will also require other maintenance as outlined in the accompanying Kohler Owner's Manual.
- VI. The fan wheel should be checked every 1,000 hours or, at a minimum, once per year. Remove the fan wheel and visually inspect it for mechanical integrity. If any aberration is detected, the fan wheel should be replaced immediately.